

MODEL	MEASUREMENT RANGE	MAXIMUM CONDUCTOR SIZE	JAW OPENING	POWER SOURCE
AMPFLEX FLEXIBLE AC CURRENT PROBES	5 to 10,000Arms SOME HAVE DUAL RANGES	8" to 15"	--	9V ALKALINE BATTERY
LOGLIFE AMPFLEX FLEXIBLE AC CURRENT PROBES	5 to 3000Arms SOME HAVE DUAL RANGES	8" & 12"	---	9V ALKALINE BATTERY
FLEXPROBE FLEXIBLE AC CURRENT PROBES	5 to 300Arms 50A to 3000Arms DUAL RANGE	8"	--	(2) 3V LITHIUM BATTERIES (CR2032)
MR400 & MR500 SERIES AC/DC CURRENT PROBES	0.2 to 1000A AC 0.4 to 1500A DC	1.18" & 1.5"	1.2" & 1.55"	--
AC/DC MICRO-PROBES	0 to 3Arms AC 0 to 4.5A DC	0.18"	1.2"	--
OSCILLOSCOPE & BNC TERMINATED PROBES	1 to 2400A AC 100mA to 1500A DC	0.46" to 2.52"	2.25 to 3.54"	--
MN100 SERIES AC CURRENT PROBES	1mA to 150A AC	0.46"	0.75"	--
MN200 & 300 SERIES AC CURRENT PROBES	0.1 to 240A AC	0.78"	0.83"	--
SL SERIES AC/DC PROBES	10mA to 120A AC 10mA to 150A DC	0.46"	2.25"	9V ALKALINE BATTERY
MD SERIES AC CURRENT PROBES	1 to 600A AC	1.18"	1.3"	--
SR SERIES AC CURRENT PROBE	0.1 to 1000A AC	2.05"	2.25"	--
JM SERIES AC CURRENT PROBE	1 to 3000A AC	2.52"	3.54"	--