



Clamp-on Meter Model 503

Economical

Cat. #2117.22

400AAC/DC, 600VAC/DC

Measures AC and DC voltage and current, continuity, and resistance. In compliance with international safety and quality standards. Data Hold function freezes the measurement.

Cat.#2117.22

Voltage Range:	600Vrms AC/DC Auto-Ranging
Resolution V Max:	0.1V
Current Range:	400Arms AC/DC
Resolution A Max:	0.01A
Accuracy V Typical:	0.8% ± 5cts
Accuracy A Typical:	1.5% ± 10cts
Continuity:	<40Ω
Resistance:	400Ω
Power Source:	2 x AAA, IEC LR3
Battery Life:	80 hours
Dimensions:	7.6 x 1.97 x 1.1" (193 x 50 x 28mm)
Weight:	8.11 oz. (230g) with batteries
Jaw Opening:	1.18" (28mm)
Operating Temperature:	+32° to 104°F (0° to +40°C)
Storage Temperature:	+14° to 140°F (-10° to +60°C)
Operating Humidity:	80% up to 104°F (40°C)
Pollution Degree:	2

For more details, download the datasheet or user manual at www.aemc.com

15 Faraday Drive • Dover, NH 03820 USA • (800) 343-1391 • (603) 749-6434 • www.aemc.com

customerservice@aemc.com • techsupport@aemc.com

For more details, download the datasheet or user manual at www.aemc.com

15 Faraday Drive • Dover, NH 03820 USA • (800) 343-1391 • (603) 749-6434 • www.aemc.com
customerservice@aemc.com • techsupport@aemc.com