



Clamp-on Meter Model 605

Large Size, Professional Functionality

Cat. #2139.60

TRMS, True InRush[®], 1000V_{AC/DC}, 2000A_{AC} /3000A_{DC}

Measures AC, DC and AC+DC voltage, current, and power. Also measures frequency, resistance, continuity, True InRush[®], and phase rotation. Performs diode checks. Delta relative function allows new measurements to be compared to a reference value. Safety rated at 1000V CAT IV. IP54 rated to withstand dust and water spray.

Cat.#2139.60

Voltage Range:	1000Vrms AC/DC/AC+DC Autoranging
Resolution Max:	0.01V
Current Range:	2000Arms AC, 3000ADC
Resolution Max:	0.01A
Accuracy V Typical:	1% ± 3cts
Accuracy A Typical:	1% ± 3cts
True InRush [®] :	10 to 1000AAC, 10 to 1500ADC
Power Measurement Max:	2MW AC, 3MW DC
THD:	Yes, %f and %r
Continuity:	Selectable from 0 to 999.9Ω
Resistance:	100kΩ
Diode Test:	0 to 3.2VDC
Frequency:	20kHz in V, 2kHz in A
Power Factor:	Yes
Phase Order:	Yes
MIN/MAX/PEAK-/PEAK+	Yes
ΔREL:	Yes
Power Source:	4 x AA, NEDA 15A, IEC LR6
Battery Life:	>350 hours
Dimensions:	11.65 x 4.37 x 1.61" (296 x 111 x 41mm)

For more details, download the datasheet or user manual at www.aemc.com

15 Faraday Drive • Dover, NH 03820 USA • (800) 343-1391 • (603) 749-6434 • www.aemc.com

customerservice@aemc.com • techsupport@aemc.com

Weight:	1.4 lbs (640g) with batteries
Jaw Opening:	2.36" (60mm)
Operating Temperature:	-4° to +131°F (-20 to +55°C)
Storage Temperature:	-40° to +158°F (-40 to +70°C)
Operating Humidity:	90% up to 131°F (55°C)
Pollution Degree:	2
Ingress Protection:	IP54
EMC:	EN61326-1
Safety Compliance:	EN/IEC 61010-1 to 1000V CAT IV EN/IEC 61010-2-030:2010 EN/IEC 61010-032:2002

For more details, download the datasheet or user manual at www.aemc.com

15 Faraday Drive • Dover, NH 03820 USA • (800) 343-1391 • (603) 749-6434 • www.aemc.com
customerservice@aemc.com • techsupport@aemc.com

