



## Power Clamp-on Meter Model 607

### Large Size, Professional Functionality

Cat. #2139.61

**TRMS, True InRush®, 1000 V<sub>AC/DC</sub>, 2000 A<sub>AC</sub> /3000 A<sub>DC</sub>, Data Recording**

Measures AC, DC and AC+DC voltage, current, and power. Also measures frequency, resistance, continuity, True InRush®, and harmonics. Performs diode checks. Performs data recording. Safety rated at 1000 V CAT IV. IP54 rated to withstand dust and water spray.

Cat.#2139.61

|                               |  |
|-------------------------------|--|
| <b>Voltage Range:</b>         | 1000 Vrms AC/DC / AC+DC Autoranging                |
| <b>Resolution Max:</b>        | 0.01 V   |
| <b>Current Range:</b>         | 2000 Arms AC, 3000 ADC                             |
| <b>Resolution Max:</b>        | 0.01 A   |
| <b>Accuracy V Typical:</b>    | 1 % ± 3 cts  |
| <b>Accuracy A Typical:</b>    | 1 % ± 3 cts  |
| <b>True InRush®:</b>          | (20 to 2000) AAC, 20 to 3000 ADC                   |
| <b>Power Measurement Max:</b> | 2 MW AC, 3 MW DC                                   |
| <b>Harmonics:</b>             | Up to 25 <sup>th</sup>                             |
| <b>THD:</b>                   | Yes, % f and % r                                   |
| <b>Continuity:</b>            | Selectable from (0 to 999.9) Ω                     |
| <b>Resistance:</b>            | 100 kΩ   |
| <b>Frequency:</b>             | 20 kHz in V, 2 kHz in A                            |
| <b>Power Factor:</b>          | Yes  |
| <b>Phase Order:</b>           | Yes  |
| <b>MIN/MAX/PEAK-/PEAK+</b>    | Yes  |
| <b>ΔREL:</b>                  | Yes  |
| <b>Recording:</b>             | Yes, up to 1000 points (160 h at 10 min intervals) |
| <b>Communication:</b>         | Bluetooth  |
| <b>Software:</b>              | Yes, DataView included                             |
| <b>Power Source:</b>          | (4) AA, NEDA 15 A, IEC LR6                         |

For more details, download the datasheet or user manual at [www.aemc.com](http://www.aemc.com)

15 Faraday Drive • Dover, NH 03820 USA • (800) 343-1391 • (603) 749-6434 • [www.aemc.com](http://www.aemc.com)

[customerservice@aemc.com](mailto:customerservice@aemc.com) • [techsupport@aemc.com](mailto:techsupport@aemc.com)

|                               |   |
|-------------------------------|---|
| <b>Battery Life:</b>          | > 350 h   |
| <b>Dimensions:</b>            | (10.7 x 3.6 x 1.6) in (272 x 92 x 41) mm                                  |
| <b>Weight:</b>                | 1.4 lbs (640 g) with batteries  |
| <b>Jaw Opening:</b>           | 2.36 in (60 mm)   |
| <b>Operating Temperature:</b> | (-4 to 131) °F (-20 to +55) °C  |
| <b>Storage Temperature:</b>   | (-40 to 158) °F (-40 to +70) °C   |
| <b>Operating Humidity:</b>    | 90 % up to 131 °F (55 °C)   |
| <b>Pollution Degree:</b>      | 2   |
| <b>Ingress Protection:</b>    | IP54  |
| <b>EMC:</b>                   | EN61326-1   |
| <b>Safety Compliance:</b>     | EN/IEC 61010-1 to 1000 V CAT IV<br>EN/IEC 61010-2-030<br>EN/IEC 61010-032 |



For more details, download the datasheet or user manual at [www.aemc.com](http://www.aemc.com)

15 Faraday Drive • Dover, NH 03820 USA • (800) 343-1391 • (603) 749-6434 • [www.aemc.com](http://www.aemc.com)  
[customerservice@aemc.com](mailto:customerservice@aemc.com) • [techsupport@aemc.com](mailto:techsupport@aemc.com)

