



Clamp-on Meter Model CM605

Cat. #7000.02

100A AC/DC, Low Current Measurement

A good choice for both process and general industrial applications. It can detect milliamp process signals, as well as the higher currents up to 100A associated with general industrial monitoring and troubleshooting.

Cat.#7000.02

Voltage Range:	600V AC/DC Auto-Ranging
Resolution Max:	0.1V
Current Range:	100A AC/DC
Resolution Max:	0.001A
Accuracy V Typical:	1.5% ± 5cts
Accuracy A Typical:	2% ± 10cts
Continuity:	<100Ω
Resistance:	10kΩ
ΔREL:	Yes
Power Source:	2 x AAA, IEC LR03
Dimensions:	7.44 x 2.8 x 1.46" (189 x 71 x 37mm)
Weight:	6.5 oz. (180g)
Jaw Opening:	0.45" (12mm)
Operating Temperature:	+32° to 104°F (0 to +40°C)
Storage Temperature:	+14° to 140°F (-10 to +60°C)
Operating Humidity:	80% up to 104°F (40°C)
Pollution Degree:	2

For more details, download the datasheet or user manual at www.aemc.com

15 Faraday Drive • Dover, NH 03820 USA • (800) 343-1391 • (603) 749-6434 • www.aemc.com

customerservice@aemc.com • techsupport@aemc.com

For more details, download the datasheet or user manual at www.aemc.com

15 Faraday Drive • Dover, NH 03820 USA • (800) 343-1391 • (603) 749-6434 • www.aemc.com
customerservice@aemc.com • techsupport@aemc.com