

AmpFlex[®] Flexible Sensor 193-24-BK



AmpFlex[®] Sensor 24" Model 193-24-BK for use with Models 3945/3945-B, 8220, 8230, 8333, 8335, 8336, 8435, 8436 & PEL Series is used to measure the current flowing in a conductor or bus bar without opening the circuit. It also insulates the user from dangerous voltages in the circuit.

Cat.#2140.34

Clamping Diameter	7.64" (190mm)
Current Range	12,000AAC
Measurement Range	100mA to 12,000AAC
Lead Length	10 ft (3m)
Output Termination	Proprietary connector
Accuracy (Typical)	±1%
Power Source	N/A
Compatibility	AEMC PowerPads and PELs (limited range with models 8220, 8230, 8435)
Dimensions	6.6 x 6.2 x 0.98" (170 x 158 x 25mm)
Weight	7.7oz (270g)
Operating Temperature	14° to +131°F (-10° to +55°C); 10 to 85% RH
Storage Temperature	-40° to +158°F (-40° to +70°C); 10 to 90% RH
Pollution Degree	2
Protection	IK 04, IP 65

For more details, download the datasheet or user manual at www.aemc.com

15 Faraday Drive • Dover, NH 03820 USA • (800) 343-1391 • (603) 749-6434 • www.aemc.com
customerservice@aemc.com • techsupport@aemc.com

For more details, download the datasheet or user manual at www.aemc.com

15 Faraday Drive • Dover, NH 03820 USA • (800) 343-1391 • (603) 749-6434 • www.aemc.com
customerservice@aemc.com • techsupport@aemc.com