

AC Current Probe Model C177A



Cat. #2138.52

200A, Lead

Current probe with a measurement range of 5mA to 200A, and transformation ratio of 10,000:1. Maximum clamping diameter is 2.05" (52mm). Includes 6.5' (2m) lead with proprietary CA connector. Designed for Multi-Function Installation Testers Models C.A 6116/6116N, and C.A 6117.

| | |
|------------------------------------|---|
| Meter Compatibility | C.A 6116N, C.A 6117 |
| Maximum Clamping Diameter | 2.05" (52mm) |
| Current Range | 200A |
| Measurement Range | 5mA to 200A |
| Transformation Ratio | 10,000:1 |
| Output | 6.5ft (2m) lead with proprietary CA connector |
| Operating Temperature | 32° to +113°F (0° to +45°C); 90% RH |
| Storage Temperature | -40° to +158°F (-40° to +70°C) |
| Operating Relative Humidity | 90% RH |
| Dimensions (HxWx D) | 8.50 x 4.37 x 1.77" (216 x 111 x 45mm) |
| Weight | 1.21 lb (550g) |
| Pollution Degree | 2 |
| Ingress Protection | IP 40, IP 30 with jaws open |

For more details, download the datasheet or user manual at www.aemc.com

For more details, download the datasheet or user manual at www.aemc.com