

AC Current Probe Model JM865A



Cat. #2110.88

1000A, 5mA/A; 2000A, 2.5mA/A & 3000A, 1.666mA/A, Jack

Features excellent transformation and low phase shift. Provides accurate measurements up to 1000AAC/2000AAC/3600AAC. The "squared" jaw permits multiple conductor or bus bar positionings. Provides excellent TRMS capabilities and reliable signal reproduction.

Maximum Conductor Size	Cable: 2.52" (64mm) Bus bar: 1.97 x 5.31" (50 x 135mm), 2.52 x 3.94" (64 x 100mm)
Current Range	1000AAC; 2000AAC; 2400AAC (3000AAC if ambient temperature <95°F / 35°C)
Measurement Range	1 to 1000AAC; 1 to 2000AAC; 1 to 2400AAC (3000AAC if ambient temperature <95°F / 35°C)
Output Signal	5mAAC / AAC (5A @ 1000A); 2.5mAAC / AAC (5A @ 2000A); 1.666mAAC / AAC (5A @ 3000A)
Transformation Ratio	1000:5; 2000:5; 3000:5
Output	4mm safety banana jack
Accuracy 50/60Hz	1% @ 1000A; 0.5% @ 2000A; 0.5% @ 3000A
Frequency Range	30Hz to 1.5kHz
Phase Shift	1° @ 1000A; 0.5° @ 2000A; 0.5° @ 3000A
Load Impedance	0.1Ω @ 1000A; 0.2Ω @ 2000A; ≤2Ω @ 3000A
Overload	1200A for 10min @ 1000A; 2400A for 10min @2000A; 3600A for 10min @ 3000A
Operating Temperature	+14° to +122°F (-10° to +50°C)
Storage Temperature	-13° to +176°F (-25° to +80°C)
Dimensions (HxWxD)	4.72 x 12.40 x 1.9" (120 x 315 x 48mm)
Weight	2.65 lbs (1200g)
Pollution Degree	2
Rating	UL 94 V0 (handles), ABS UL 94 V2 (jaws)
Ingress Protection	IP 20

For more details, download the datasheet or user manual at www.aemc.com

For more details, download the datasheet or user manual at www.aemc.com