

MiniFlex® Sensor Model MA193-14-BK (refurbished)

MiniFlex® Sensor Model MA193-14-BK for Models 3945-B, 8220, 8230, 8333, 8335, 8336, 8435 & PEL Series

Cat.#901.2140.50



Clamping Diameter	2.75" (70mm)
Current Range	3000AAC
Measurement Range	0.1 to 3000AAC (10,000A peak)
Lead Length	10 ft (3m)
Output Termination	Proprietary connector
Accuracy (Typical)	1%
Power Source	N/A
Compatibility	AEMC PowerPads and PELs (limited range with models 8220, 8230, 8435)
Operating Temperature	14° to +131°F (-10° to +55°C); 10 to 85% RH
Storage Temperature	-40° to +158°F (-40° to +70 °C); 10 to 90% RH
Dimensions	4 x 2.5 x 1.1" (103 x 63 x 28mm)
Weight	1.94 oz (55g)
Pollution Degree	2
Protection	IK 04, IP 40

For more details, download the datasheet or user manual at www.aemc.com

15 Faraday Drive • Dover, NH 03820 USA • (800) 343-1391 • (603) 749-6434 • www.aemc.com
customerservice@aemc.com • techsupport@aemc.com

For more details, download the datasheet or user manual at www.aemc.com

15 Faraday Drive • Dover, NH 03820 USA • (800) 343-1391 • (603) 749-6434 • www.aemc.com
customerservice@aemc.com • techsupport@aemc.com