

## MiniFlex<sup>®</sup> Sensor Model MA194-24-BK (Replaces Cat. #2140.78)



MiniFlex<sup>®</sup> Sensor Model MA194-24-BK (Waterproof, IP67) for Models 3945/3945-B, 8220, 8230, 8333, 8335, 8336, 8435, 8436, and the PEL Series (Replaces Cat. #2140.78)

Cat.#2140.80

Clamping Diameter	24 in (609 mm)
Current Range	3000 AAC
Measurement Range	0.1 to 3000 AAC (10,000 A peak)
Lead Length	10 ft (3 m)
Output Termination	Proprietary connector
Accuracy (Typical)	1%
Power Source	N/A
Compatibility	AEMC PowerPads and PELs (limited range with models 8220, 8230, 8435)
Operating Temperature	(14 to +131) °F (-10 to +55) °C; (10 to 85) % RH
Storage Temperature	(-40 to +158) °F (-40 to +70) °C; (10 to 90) % RH
Dimensions	(4 x 2.5 x 1.1) in (103 x 63 x 28) mm
Weight	1.94 oz (55 g)
Pollution Degree	2
Protection	IK 04, IP 40

For more details, download the datasheet or user manual at [www.aemc.com](http://www.aemc.com)

15 Faraday Drive • Dover, NH 03820 USA • (800) 343-1391 • (603) 749-6434 • [www.aemc.com](http://www.aemc.com)  
[customerservice@aemc.com](mailto:customerservice@aemc.com) • [techsupport@aemc.com](mailto:techsupport@aemc.com)

For more details, download the datasheet or user manual at [www.aemc.com](http://www.aemc.com)

15 Faraday Drive • Dover, NH 03820 USA • (800) 343-1391 • (603) 749-6434 • [www.aemc.com](http://www.aemc.com)  
[customerservice@aemc.com](mailto:customerservice@aemc.com) • [techsupport@aemc.com](mailto:techsupport@aemc.com)

