

AC Current Probe Model MD304 (Refurbished)



Cat. #901.1201.37

600A, 10mA/A, Lead

High accuracy 600A current probe with excellent frequency and phase shift characteristics. Unique hook-shaped jaws enable the user to "pry" into or "hook" onto cables. Maximum conductor size is 2 x 500kcmil. Works as a traditional current transformer with ratio of 1000:1. Includes 5' (1.5m) lead with safety banana plugs.

Maximum Conductor Size	Cable 1.18" (30mm), bus bar 2.48x0.19" (63 x 5mm), dual cable 0.98" (25mm)
Current Range	600AAC
Measurement Range	1 to 600AAC
Output Signal	10mAAC / AAC (6AAC @ 600AAC)
Transformation Ratio	100:1
Output	Insulated 5ft (1.5m) lead with safety 4mm banana plugs
Accuracy 50/60 Hz	3% @ 600A
Frequency Range	48Hz to 1KHz
Phase Shift	3°
Load Impedance	0.1Ω max
Overload	700A for 10 min
Operating Temperature	-5° to +122°F (-15° to +50°C)
Storage Temperature	-40° to +185°F (-40° to +85°C)
Dimensions	2.6 x 7.68 x 1.34" (66 x 195 x 34mm)
Weight	14.82 oz (420g)
Pollution Degree	2
Rating	UL 94 V0
Ingress Protection	IP 20
EMC	EN 50081-1 Class B, EN 50082-2, IEC 1000-4-2

For more details, download the datasheet or user manual at www.aemc.com

For more details, download the datasheet or user manual at www.aemc.com