

AC Current Probe Model MD305



Cat. #1201.36

600A, 1mA/A, Lead

High accuracy 600A current probe with excellent frequency and phase shift characteristics. Unique hook-shaped jaws enable the user to "pry" into or "hook" onto cables. Maximum conductor size is 2 x 500kcmil. Works as a traditional current transformer with ratio of 1000:1. Includes 5' (1.5m) lead with safety banana plugs.

Cat.#1201.36

Maximum Conductor Size	Cable 1.18" (30mm), bus bar 2.48x0.19" (63 x 5mm), dual cable 0.98" (25mm)
Current Range	600AAC
Measurement Range	1 to 600AAC
Output Signal	1mAAC / AAC (600mAAC @ 600AAC)
Transformation Ratio	1000:1
Output	Double insulated 5ft (1.5m) lead with safety 4mm banana plugs
Accuracy 50/60Hz	2% @ 600A
Frequency Range	40Hz to 1KHz
Phase Shift	1°
Load Impedance	5Ω max
Overload	700A for 10 min
Operating Temperature	-5° to +122°F (-15° to +50°C)
Storage Temperature	-40° to +185°F (-40° to +85°C)
Dimensions	2.6 x 7.68 x 1.34" (66 x 195 x 34mm)
Weight	14.82 oz (420g)
Pollution Degree	2
Rating	UL 94 V0
Ingress Protection	IP 20
EMC	EN 50081-1 Class B, EN 50082-2, IEC 1000-4-2

For more details, download the datasheet or user manual at www.aemc.com

15 Faraday Drive • Dover, NH 03820 USA • (800) 343-1391 • (603) 749-6434 • www.aemc.com

customerservice@aemc.com • techsupport@aemc.com

For more details, download the datasheet or user manual at www.aemc.com

15 Faraday Drive • Dover, NH 03820 USA • (800) 343-1391 • (603) 749-6434 • www.aemc.com
customerservice@aemc.com • techsupport@aemc.com

