

AC Current Probe Model MN05

Cat. #2129.19

(100AAC/0.1VAC (1mV/A, 10AAC/10VAC (1V/A), Lead)

Designed for digital multimeters, loggers, recorders, and oscilloscopes to measure AC currents in low-power secondary or industrial applications. Dual ranges (5mA to 10A_{AC} and 1 to 150A_{AC}) provide excellent resolution for measuring AC intensities. Jaw opening accommodates conductors up to 0.39" diameter. Features 48Hz to 10kHz response. Conforms to EN 61010, 600V CAT III safety standard.



Cat.#2129.19

Maximum Conductor Size	0.39" (10mm)
Current Range	10A & 100Arms AC
Measurement Range	5mA to 10A & 1A to 100A
Output	5ft (1.5m) lead with 4mm safety banana plug
Transformation Ratio	N/A
Output Signal	100AAC/0.1VAC (1mV/A, 10AAC/10VAC (1V/A)
Accuracy 50/60Hz	3% R ± 0.15mA & 2% R ± 50mA
Frequency Range	48 to 500Hz
Phase Shift At 50Hz	N/A
Open Secondary Voltage	N/A
Load Impedance	1MΩ
Overload	150A Permanent
Dimensions (H x W x D)	4.43 x 1.48 x 1.02" (112.5 x 37.5 x 26 mm)
Weight With 24" (610mm) Sensor	6.5 oz (180g)
Operating Temperature	14° to +122°F (-10° to +50°C)
Storage Temperature	-40° to +176°F (-40° to +80°C)
Operating Humidity	90% RH
Pollution Degree	2
Ingress Protection (Ip)	IP40
EMC	EN 61326-1

For more details, download the datasheet or user manual at www.aemc.com

15 Faraday Drive • Dover, NH 03820 USA • (800) 343-1391 • (603) 749-6434 • www.aemc.com

customerservice@aemc.com • techsupport@aemc.com

For more details, download the datasheet or user manual at www.aemc.com

15 Faraday Drive • Dover, NH 03820 USA • (800) 343-1391 • (603) 749-6434 • www.aemc.com
customerservice@aemc.com • techsupport@aemc.com

