

## AC Current Probe Model MN134

Cat. #2129.22 MN134 - AC current probe (10 A, 100 mV/A, Lead)

Cat.#2129.22



Maximum Clamping Diameter	0.39 in (10 mm)
Nominal Range	10 AAC
Measurement Range	1 mA to 10 AAC
Output Signal	100 mVAC / AAC (1 V @ 10 A)
Output	Double/reinforced 5 ft (1.5m) lead with 4mm safety banana plug
Accuracy 50/60Hz	1 MΩ load: 2% Reading ± 2 mA
Phase Shift at 50/60Hz	< 10°
Overload	20 A continuous
Frequency Range	(48 to 500) Hz
Load Impedance	1 MΩ min
Open Secondary Voltage	≤ 30 V
Working Voltage	600 Vrms
Common Mode Voltage	600 Vrms
Dimensions (HxWxD)	(5.12 x 1.46 x 0.874) in (130 x 37 x 25) mm
Weight	6.5 oz (180g)
Operating Temperature	(14 to 122) °F (-10° to 50) °C
Storage Temperature	(-40° to 176) °F (-40° to 80) °C
Case Protection	IP 40 (IEC 60529)

For more details, download the datasheet or user manual at [www.aemc.com](http://www.aemc.com)

15 Faraday Drive • Dover, NH 03820 USA • (800) 343-1391 • (603) 749-6434 • [www.aemc.com](http://www.aemc.com)  
[customerservice@aemc.com](mailto:customerservice@aemc.com) • [techsupport@aemc.com](mailto:techsupport@aemc.com)

For more details, download the datasheet or user manual at [www.aemc.com](http://www.aemc.com)

15 Faraday Drive • Dover, NH 03820 USA • (800) 343-1391 • (603) 749-6434 • [www.aemc.com](http://www.aemc.com)  
[customerservice@aemc.com](mailto:customerservice@aemc.com) • [techsupport@aemc.com](mailto:techsupport@aemc.com)

