AEMC® INSTRUMENTS
CHAUVIN ARNOUX GROUP

Summary Sheet

AC Current Probe Model MN193-BK



Cat. #2140.36
Measurement range:
5A: 0.005 to 6A$_{AC}$, 100A: 0.1 to 120A$_{AC}$
AC current probe for use with Models 3945/3945-B, 8220, 8230, 8333, 8335, 8336, PEL Series, L104 and L564.

Cat.#2140.36

Clamping Diameter	0.78” (20mm)
Current Range	5A & 100AAC
Measurement Range	5mA to 6A AC & 200mA to 120AAC
Lead Length	10 ft (3m)
Output Termination	Proprietary connector
Accuracy (Typical)	±1%
Power Source	N/A
Compatibility	AEMC PowerPads and PELs
Operating Temperature	14° to +131°F (-10° to +55°C); 10 to 85% RH
Storage Temperature	-40° to +158°F (-40° to +70 °C); 10 to 90% RH
Dimensions	5.47 x 2.0 x 1.18” (135 x 51 x 30mm)
Weight	24 oz (690g)
Pollution Degree	2
Protection	IK 04, IP40 (jaws closed), IP30 (jaws open)

For more details, download the datasheet or user manual at www.aemc.com

15 Faraday Drive • Dover, NH 03820 USA • (800) 343-1391 • (603) 749-6434 • www.aemc.com
customerservice@aemc.com • techsupport@aemc.com

AEMC® INSTRUMENTS
CHAUVIN ARNOUX GROUP

Copyright @2024 Chauvin Arnoux®, Inc. d.b.a AEMC® Instruments

Safety Compliance	IEC 61010-1, IEC 61010-2-032, 600V CAT III, 300V CAT IV

For more details, download the datasheet or user manual at www.aemc.com

15 Faraday Drive • Dover, NH 03820 USA • (800) 343-1391 • (603) 749-6434 • www.aemc.com
customerservice@aemc.com • techsupport@aemc.com

Copyright @2024 Chauvin Arnoux®, Inc. d.b.a AEMC® Instruments