



## AC Current Probe Model MN77

Cat. #2138.53

200A, Lead

Current probe with a measurement range of 5mA to 20A, and transformation ratio of 1000:1. Maximum clamping diameter is 0.78" (20mm). Includes 6.5' (2m) lead with proprietary CA connector. Designed for Multi-Function Installation Testers Models C.A 6116/6116N, and C.A 6117.

Cat.#2138.53

Meter Compatibility	C.A 6116N, C.A 6117
Maximum Clamping Diameter	0.78" (20mm)
Current Range	20A
Measurement Range	5mA to 20A
Transformation Ratio	1000:1
Output	6.5ft (2m) lead with proprietary CA connector
Operating Temperature	32° to +113°F (0° to +45°C); 90% RH
Storage Temperature	-40° to +158°F (-40° to +70°C)
Dimensions (HxWxD)	5.31 x 2.01 x 1.18" (135 x 51 x 30mm)
Weight	6.35 oz (180g)
Pollution Degree	2
Ingress Protection	IP 40, IP 30 with jaws open

For more details, download the datasheet or user manual at [www.aemc.com](http://www.aemc.com)

15 Faraday Drive • Dover, NH 03820 USA • (800) 343-1391 • (603) 749-6434 • [www.aemc.com](http://www.aemc.com)

[customerservice@aemc.com](mailto:customerservice@aemc.com) • [techsupport@aemc.com](mailto:techsupport@aemc.com)

For more details, download the datasheet or user manual at [www.aemc.com](http://www.aemc.com)

15 Faraday Drive • Dover, NH 03820 USA • (800) 343-1391 • (603) 749-6434 • [www.aemc.com](http://www.aemc.com)  
[customerservice@aemc.com](mailto:customerservice@aemc.com) • [techsupport@aemc.com](mailto:techsupport@aemc.com)