



## AC Current Probe Model MN77

Cat. #2138.53

200A, Lead

Current probe with a measurement range of 5mA to 20A, and transformation ratio of 1000:1. Maximum clamping diameter is 0.78" (20mm). Includes 6.5' (2m) lead with proprietary CA connector. Designed for Multi-Function Installation Testers Models C.A 6116/6116N, and C.A 6117.

<b>Meter Compatibility</b>	C.A 6116N, C.A 6117
<b>Maximum Clamping Diameter</b>	0.78" (20mm)
<b>Current Range</b>	20A
<b>Measurement Range</b>	5mA to 20A
<b>Transformation Ratio</b>	1000:1
<b>Output</b>	6.5ft (2m) lead with proprietary CA connector
<b>Operating Temperature</b>	32° to +113°F (0° to +45°C); 90% RH
<b>Storage Temperature</b>	-40° to +158°F (-40° to +70°C)
<b>Dimensions (HxWxD)</b>	5.31 x 2.01 x 1.18" (135 x 51 x 30mm)
<b>Weight</b>	6.35 oz (180g)
<b>Pollution Degree</b>	2
<b>Ingress Protection</b>	IP 40, IP 30 with jaws open
<b>Safety Compliance</b>	IEC 61010-2-032, EN 61010-1, EN61010-031 300V CAT IV, 600V CAT III



For more details, download the datasheet or user manual at [www.aemc.com](http://www.aemc.com)