



AC Current Probe Model MN94 (Used only with models 8345 and PEL52)

Cat. #2140.81

AC Current Probe Model MN94 (50 mA 200 AAC) used only with models 8345 and PEL 52/p>

Cat.#2140.81

Maximum Conductor Size	0.25" (16 mm)
Current Range	50 mA 200 AAC
Frequency Range	(48 to 65) Hz
Dimensions (H x W x D)	(5.12 x 1.81 x 1.34) in (130 x 46 x 34) mm
Weight	8.82 oz (250g)
Sensor length	10 ft (3 m)
Type of current sensor	Type A
Operating Temperature	(14 to 131) °F (-10 to 55) °C
Storage Temperature	(-40 to 158) °F (-40 to 70) °C
Operating Humidity	(10 to 85) % RH
Storage Humidity	(10 to 90) % RH
Double Insulated	Yes
Ingress Protection (Ip)	IP20
Pollution Degree	2
Electromagnetic Compatibility (EMC)	EN/IEC 61326-1
Safety Compliance	EN/IEC 61010-2-032 600 V CAT III, 300 V CAT IV



For more details, download the datasheet or user manual at www.aemc.com

15 Faraday Drive • Dover, NH 03820 USA • (800) 343-1391 • (603) 749-6434 • www.aemc.com
customerservice@aemc.com • techsupport@aemc.com

For more details, download the datasheet or user manual at www.aemc.com

15 Faraday Drive • Dover, NH 03820 USA • (800) 343-1391 • (603) 749-6434 • www.aemc.com
customerservice@aemc.com • techsupport@aemc.com