

## AC Current Probe Model SR193-BK

Cat. #2140.33

1 to 1200AAC

AC current probe measures up to 1200AAC. Designed for use with Power Quality Analyzers Models 3945/3945B, 8220, 8230, 8333, 8335, and 8336, the PEL 100 Series and Simple Logger II Models L104 and L564.



Cat.#2140.33

Clamping Diameter	2" (52mm)
Current Range	1200AAC
Measurement Range	1 to 1200AAC
Lead Length	10 ft (3m)
Output Termination	Proprietary connector
Accuracy (Typical)	±0.3%
Power Source	N/A
Compatibility	AEMC PowerPads and PELs
Operating Temperature	14° to +131°F (-10° to +55°C); 10 to 85% RH
Storage Temperature	-40° to +158°F (-40° to +70°C); 10 to 90% RH
Dimensions	8.5 x 4.4 x 1.8" (216 x 111 x 45mm)
Weight	24 oz (690g)
Pollution Degree	2
Protection	IK 04, IP40 (jaws closed), IP30 (jaws open)

For more details, download the datasheet or user manual at [www.aemc.com](http://www.aemc.com)

15 Faraday Drive • Dover, NH 03820 USA • (800) 343-1391 • (603) 749-6434 • [www.aemc.com](http://www.aemc.com)

[customerservice@aemc.com](mailto:customerservice@aemc.com) • [techsupport@aemc.com](mailto:techsupport@aemc.com)

For more details, download the datasheet or user manual at [www.aemc.com](http://www.aemc.com)

15 Faraday Drive • Dover, NH 03820 USA • (800) 343-1391 • (603) 749-6434 • [www.aemc.com](http://www.aemc.com)  
[customerservice@aemc.com](mailto:customerservice@aemc.com) • [techsupport@aemc.com](mailto:techsupport@aemc.com)