

## Ground Resistance Tester Model 3640 DISCONTINUED



Cat. #2114.92

Range 0.01 to 2000Ω, Resolution 0.001 to 10Ω, 4-Point test

The Digital Ground Resistance Tester Model 3640 performs ground resistance measurement. This direct reading tester is auto-ranging, so it automatically seeks out the optimum measurement range. The Model 3640 is easy to use - simply connect the leads, press to measure, and read. The large LCD (nearly 3/4" high) also indicates low battery status, overrange, and lead reversals.

The Ground Resistance Tester Model 3640 is also available in complete Kits (150ft & 300ft).

Cat.#2114.92

Range (Auto-ranging)	0 to 2000Ω
Resolution	0.01 to 1Ω
Test Current	0.1 to 10mA
Accuracy Typical	±(2% R +1ct)
Open Voltage	42V peak
Operating Frequency	128Hz square wave
Interference	Rejection to high levels of interference voltage (DC, 50/60Hz, harmonics)
Maximum Auxiliary Rod Resistance	<b>Current Circuit:</b> 3kΩ @ 20Ω range 30kΩ @ 200Ω range 50kΩ @ 2000Ω range
	<b>Voltage Circuit:</b> 50kΩ on all ranges
Response Time	6 seconds for a stabilized measurement
Display	200 counts, 7 segment LCD
Power Source	8 x 1.5V AA alkaline batteries
Battery Life	1800 15-seconds tests
Operating Temperature	14° to 131°F (-10° to 55°C)
Storage Temperature	-40° to 158°F (-40° to 70°C)
Relative Humidity	Up to 90%

For more details, download the datasheet or user manual at [www.aemc.com](http://www.aemc.com)

15 Faraday Drive • Dover, NH 03820 USA • (800) 343-1391 • (603) 749-6434 • [www.aemc.com](http://www.aemc.com)

[customerservice@aemc.com](mailto:customerservice@aemc.com) • [techsupport@aemc.com](mailto:techsupport@aemc.com)

<b>Dimensions</b>	8.7 x 5.4 x 5.9" (220 x 136 x 150mm)
<b>Weight (with Battery)</b>	2.9 lbs (1.3kg)
<b>Case</b>	UL 94 material
<b>Ingress Protection (IP)</b>	IP 50
<b>EMC</b>	EN 61326-1
<b>Safety Compliance</b>	EN 61010-1, 42V CAT III, Pollution Degree 2 <span style="float: right;">CE</span>

For more details, download the datasheet or user manual at [www.aemc.com](http://www.aemc.com)

15 Faraday Drive • Dover, NH 03820 USA • (800) 343-1391 • (603) 749-6434 • [www.aemc.com](http://www.aemc.com)  
[customerservice@aemc.com](mailto:customerservice@aemc.com) • [techsupport@aemc.com](mailto:techsupport@aemc.com)

