

Summary Sheet



Ground Resistance Tester Model 4620

Cat. #2130.43

Range 0.01 to 2000 Ω , Resolution 0.001 to 10 Ω , 4-Point test

The Digital Ground Resistance Tester Model 4620 performs ground resistance and soil resistivity tests. This direct reading testers measures from 0 to 2000Ω , and is auto-ranging, so it automatically seeks outs the optimum measurement range.

The Ground Resistance Tester Model 4620 is also available in complete Kits (150ft, 300ft & 500 ft).

Cat.#2130.43

Range (Auto-ranging)	0 to 2000Ω
Resolution	0.01 to 1Ω
Test Current	0.1 to 10mA
Accuracy Typical	±(2% Reading +1ct)
Open Voltage	42V peak
Withstanding Voltage	250V AC or 100V DC
Operating Frequency	128Hz square wave
Interference	Rejection to high levels of interference voltage (DC, 50/60Hz, harmonics)
Maximum Auxiliary Rod Resistance	Current Circuit: $3k\Omega$ @ 20Ω range $30k\Omega$ @ 200Ω range $50k\Omega$ @ 2000Ω range
	Voltage Circuit: 50kΩ on all ranges
Response Time	4 to 8 seconds for a stabilized measurement
Display	200 counts, 7 segment LCD, backlight
Power Source	8 x 1.5V C alkaline batteries
Battery Life	4500 15-seconds tests, low battery indicator
Dimensions	10.8 x 9.7 x 5.0" (273 x 247 x 127mm)
Weight (with Battery)	6.28 lbs (2.85kg)

For more details, download the datasheet or user manual at www.aemc.com

15 Faraday Drive • Dover, NH 03820 USA • (800) 343-1391 • (603) 749-6434 • www.aemc.com <u>customerservice@aemc.com</u> • techsupport@aemc.com



Operating Temperature	14° to 131°F (-10° to 55°C)
Storage Temperature	-40° to 158°F (-40° to 70°C)
Relative Humidity	Up to 90%
Ingress Protection (IP)	IP 65 (closed); IP 63 (open)
EMC	EN 61326-1
Safety Compliance	EN 61557, EN 61010-1, 30V CAT III, Pollution Degree 2

For more details, download the datasheet or user manual at www.aemc.com

15 Faraday Drive • Dover, NH 03820 USA • (800) 343-1391 • (603) 749-6434 • www.aemc.com <u>customerservice@aemc.com</u> • <u>techsupport@aemc.com</u>

