


Ground Resistance Tester Model 6422 (Digital, 3-Point)



Cat. #2135.55

Range 0.5 to 50Ω, Automatic Test Current 20mA max, ±10V peak open Voltage, >1500 measurements @100Ω in 3 P mode

The Digital Ground Resistance Tester Model 6422 performs 2-pole and 3-pole ground resistance measurement. This direct reading tester is auto-ranging, so it automatically seeks out the optimum measurement range.

Cat.#2135.55

Ground Resistance (2P Mode)				
Measurement Range	0.05-99.99Ω	80.0-999.9Ω	0.800-9.999kΩ	8.00-50.00kΩ
Resolution	0.01Ω	0.1Ω	1Ω	0Ω
Intrinsic Uncertainty	± (2%R + 10 ct)	± (2%R + 2 ct)	±(2%R + 1 ct)	±(2%R + 1 ct)
Ground Resistance (3P Mode)				
Measurement Range	0.50-99.99Ω	80.00-999.99Ω	0.800-2.000kΩ	—
Resolution	0.01Ω	0.1Ω	1Ω	—
Intrinsic Uncertainty	± (1%R + 10ct)	± (1%R + 2ct)	± (1%R + 1ct)	—
Measurement Frequency	128Hz or 256Hz (automatically selected)			
No-load Voltage	±10 V peak			
Maximum Test Current	20mA			
Measurement Mode	One shot or continuous			
GENERAL				
Display	Backlit LCD			
Measurement Mode	2P (Ω), 3P (Ω)			
Power Supply	(6) AA Alkaline batteries			
Battery Life	> 2,000 x 3P earth measurements at 100 Ω			
Dimensions	8.78 x 4.96 x 2.75" (223 x 126 x 70mm)			

For more details, download the datasheet or user manual at www.aemc.com

15 Faraday Drive • Dover, NH 03820 USA • (800) 343-1391 • (603) 749-6434 • www.aemc.com

customerservice@aemc.com • techsupport@aemc.com

SAFETY

Safety Ratings

EMC: IEC 61326-1; IEC 61010-2-030 / 600 V CAT IV

For more details, download the datasheet or user manual at www.aemc.com

15 Faraday Drive • Dover, NH 03820 USA • (800) 343-1391 • (603) 749-6434 • www.aemc.com
customerservice@aemc.com • techsupport@aemc.com