



Megohmmeter Model 5070

Cat. #2130.30

Graphical, Analog Bargraph, Backlight, Alarm, Timer, 500V, 1000V, 2500V, 5000V, Ramp, Auto DAR/PI/DD, RS-232 w/DataView® Software

Fully automated 5000V graphical insulation tester. Selectable and programmable test voltage (40 to 5100V). Programmable temperature correction of resistance readings. Allows programming up to three step voltage profiles, each containing up to five steps. RS-232 interface allows connection to a computer running DataView® for configuring the instrument and downloading test results and generating reports.

Cat.#2130.30

AC/DC Voltage Measurement	
Range	1 to 4000V
Accuracy	1 to 99.9V: $\pm(1\% R + 5ct)$ 100 to 4000V: $\pm(1\% R + 3ct)$
Resolution	1 to 99.9V: 0.1V 100 to 999V: 1V 1000 to 4000V: 2V
Frequency Range	1 to 2500V: DC or 15 to 500Hz 2501 to 4000V: DC
Input Impedance	750k Ω or 3M Ω (range dependent)
Insulation Measurement	
Test Voltage / Resistance Range	500V: 30k Ω to 2T Ω 1000V: 100k Ω to 4T Ω 2500V: 100k Ω to 10T Ω 5000V: 300k Ω to 10T Ω
Measurement Accuracy	30k Ω to 39.99G Ω : $\pm(5\% R + 3ct)$ 40.0G Ω 10T Ω : $\pm(15\% R + 10ct)$
Variable Voltage	40 to 5,100V
Auto Discharge	Discharge time < 7s/ μ F from Vtest to 25V @ 5000V
Live Circuit Indicator	Test inhibition if terminal voltage > 3, 10, 20% (selectable by user) of test voltage
General Features	
Programmable Alarm	Yes

For more details, download the datasheet or user manual at www.aemc.com

15 Faraday Drive • Dover, NH 03820 USA • (800) 343-1391 • (603) 749-6434 • www.aemc.com
customerservice@aemc.com • techsupport@aemc.com

DAR – PI – DD – R(t)	Yes
Ramp Mode	No
Step Mode	Up to 5 steps (voltage and duration configurable for each step)
Capacitance Measurement	0.005 to 49.99µf
Leakage Current Measurement	0 to 3mA
Open Circuit Voltage	≤ 1.1 x Vn ±2V (Vn ±2% in variable mode)
Memory	128kB Memory / Stores over 1500 test results
Communication	Serial port RS-232 with USB adapter
Software	DataView Software (included)
Power Supply	Rechargeable NIMH battery pack; external 85-256V, 50/60Hz
Battery Life	≥ 1500 tests at 5000V into 5MΩ with a duty cycle of 5 seconds on and 25 seconds off
Charging Time	6 hours approximately (charging allowed during tests)
Dimensions	10.63 x 9.84 x 7.09" (270 x 250 x 180mm)
Weight	9.5lbs (4.3kg)
Altitude Operating	6562' (2000m)
Operating Temperature	14° to +131°F (-10° to +55°C) ≤80% RH
Storage Temperature	-40° to +158°F (-40° to +70°C) ≤90% RH
IP Rating	IP 53
Safety Compliance	EN 61010-1, EN 61557, 1000V CAT III, Pollution Degree 2, CE

For more details, download the datasheet or user manual at www.aemc.com

15 Faraday Drive • Dover, NH 03820 USA • (800) 343-1391 • (603) 749-6434 • www.aemc.com
customerservice@aemc.com • techsupport@aemc.com

