



Micro-Ohmmeter Model 6240

Cat. #2129.80

10A, Instantaneous, Continuous, Multiple Test, Manual/Auto Temperature Compensation; includes 10A Kelvin Clips and DataView® software

Four-lead Kelvin tester measures very low resistance from $1\mu\Omega$ to 400Ω with resolutions to $1\mu\Omega$. Selectable test currents of 10 A, 1 A, 100 mA, and 10 mA, with a polarity reversal function. Tests both resistive and inductive material, and stores up to 99 measurements. Includes DataView® for configuring the instrument, downloading data, and generating reports.

Cat.#2129.80

Specifications						
Measurement Range	(5.0 to 3999) $\mu\Omega$	(4.0 to 39.99) m Ω	(40.0 -to 399.9) m Ω	(400 to 3999) m Ω	(4.0 to 39.99) Ω	(40.0 to 399.9) Ω
Resolution	1 $\mu\Omega$	10 $\mu\Omega$	100 $\mu\Omega$	1 m Ω	10 m Ω	100 m Ω
Accuracy	$\pm(0.25\%R + 2ct)$					
Measurement Current	10.2 A $\pm 2\%$	1.02 A $\pm 2\%$		102 mA $\pm 2\%$	10.2 mA $\pm 2\%$	
Open Voltage	(4 to 6) V					
Inductance	0.5 H Max					
Voltage Measurement Indication						
Measurement Range	(0.01 to 3.999) mV	(4 to 39.99) mV	(40 to 399.9) mV	(0.4 to 3.999) V	(4 to 4.70) V	
Resolution	1 μ V	10 μ V	100 μ V	1 mV	10 mV	
Current Measurement Indication						
Measurement Range	(5.0 to 39.99) mA	(40.0 to 399.9) mA	(0.4 to 3.999) A	(4 to 11.00) A		
Resolution	10 μ A	100 μ A	1 mA	10 mA		
General Specifications						
Storage Memory	99 tests, supplied with DataView® software for download and reporting					
Automatic Storage of Test Results	Yes					
Battery	Rechargeable NIMH battery pack 6V, 8.5Ah.					

For more details, download the datasheet or user manual at www.aemc.com

15 Faraday Drive • Dover, NH 03820 USA • (800) 343-1391 • (603) 749-6434 • www.aemc.com
customerservice@aemc.com • techsupport@aemc.com

Battery Life	10 A	≥ 850 tests with a duty cycle of 5 seconds on and 25s off
	1 A	≥ 3500 tests with a duty cycle of 5 seconds on and 25s off
	100 mA	≥ 4500 tests with a duty cycle of 5 seconds on and 25s off
	10 mA	≥ 5000 tests with a duty cycle of 5 seconds on and 25s off
	In standby mode	Battery life 4 to 6 months
Dimensions (L x W x H)	(10.70 x 9.76 x 7.18) in (272 x 248 x 182) mm	
Weight	10 lbs (4.5 kg)	
Operating Temperature	(14 to 131) °F (-10 to 55) °C & (10 to 85) % RH	
Storage Temperature (without battery)	(-40 to 158) °F (-40 to 70) °C & (10 to 90) % RH	
Altitude Operating	2000 m	
IP Rating	IP 54 per IEC 60529 cover closed	
Safety	IEC/EN 61010-1 category III 50V, Pollution Degree 2	



For more details, download the datasheet or user manual at www.aemc.com

15 Faraday Drive • Dover, NH 03820 USA • (800) 343-1391 • (603) 749-6434 • www.aemc.com
customerservice@aemc.com • techsupport@aemc.com

