



Phase Rotation Meter Model 6608 (Discontinued. Replaced by Cat. #2121.91 - Model 6612)

Cat. #2121.10

Operating voltages 40 to 850V_{AC} between phases, Frequency range 15 to 400HZ, Test current 1mA(Discontinued. Replaced by Cat. #2121.91 - Model 6612)

Cat.#2121.10

Phase Rotation Connection Method	Direct Connection with Color Coded Leads
Operating Voltages	40 to 850VAC Between Phases
Frequency Range	15 to 400HZ
Test Current	1mA
Phase Rotation Indicator	LCD Screen with Rotation Arrow
Power Supply	Line Powered
Dimensions	5.1 x 2.7 x 1.3" (130 x 69 x 32mm)
Weight	4.5oz (130g)
Operating Temperature	32° to 104°F (0° to 40°C)
Storage Temperature	-4° to 122°F (-20° to 50°C)
Relative Humidity	<80%
Safety Compliance	IEC 61010-1; 600V CAT III

For more details, download the datasheet or user manual at www.aemc.com

15 Faraday Drive • Dover, NH 03820 USA • (800) 343-1391 • (603) 749-6434 • www.aemc.com

customerservice@aemc.com • techsupport@aemc.com

CE Approved

Yes

For more details, download the datasheet or user manual at www.aemc.com

15 Faraday Drive • Dover, NH 03820 USA • (800) 343-1391 • (603) 749-6434 • www.aemc.com
customerservice@aemc.com • techsupport@aemc.com

