



Phase Rotation Meter Model 6612

Cat. #2121.91

Operating voltages (40 to 850) V_{AC} between phases, Frequency range (15 to 400) HZ, Test current 1 mA

Cat.#2121.91

Phase Rotation Connection Method	Direct Connection with Color Coded Leads
Operating Voltages	(40 to 850) V _{AC} Between Phases
Frequency Range	(15 to 400) Hz
Test Current	1 mA
Phase Rotation Indicator	LCD Screen with Rotation Arrow
Power Supply	Line Powered
Dimensions	(5.3 x 2.9 x 1.2) in (135 x 75 x 31) mm
Weight	4.83 oz (137 g)
Operating Temperature	(32 to 104) °F (0 to 40) °C
Storage Temperature	(-4 to 122) °F (-20 to 50) °C
Relative Humidity	(15 to 80) % RH
Safety Compliance	IEC 61010-1 and 61557-7; 600 V CAT IV, 1000 V CAT III Tightness: IP40 (as per IEC 60529)

For more details, download the datasheet or user manual at www.aemc.com

15 Faraday Drive • Dover, NH 03820 USA • (800) 343-1391 • (603) 749-6434 • www.aemc.com

customerservice@aemc.com • techsupport@aemc.com

CE Approved	Yes	
-------------	-----	--

For more details, download the datasheet or user manual at www.aemc.com

15 Faraday Drive • Dover, NH 03820 USA • (800) 343-1391 • (603) 749-6434 • www.aemc.com
customerservice@aemc.com • techsupport@aemc.com

