



## Voltage Absence Tester Model CA 773

Cat. #2121.15

Voltage Tester Model CA 773 (LEDs & Backlit Display, 12VAC ≤ U ≤ 1000VAC; 12VDC ≤ U ≤ 1400VDC)

Cat.#2121.15

Voltage Absence Testing (VAT)	
Voltage Indication - LEDs	12 to 1000Vac ; 12 to 1400Vdc
Voltage Indication - Display	1 to 1000Vac ; 1 to 1400Vdc
Frequency Range	DC, 16.67 to 800Hz
Input Impedance	>500kΩ
Max. Peak Current	3.5mA RMS
Polarity Indication	Yes
Redundant Hazardous Voltage Indication	The ELV (Extra-Low Voltage) LED indicates that the voltage is higher than the SELV (Safety Extra-Low Voltage) with the rate at which it flashes proportional to the voltage level.
Stray Voltage Detection	Yes (by low-impedance load switching)
RCD Tripping	Yes (by low-impedance load switching)
Phase/Neutral Identification	>50V (45 to 65HZ) ; >150V (16.67 to 45Hz)
<b>Continuity &amp; Resistance</b>	
Buzzer Trigger Threshold	100Ω typical (150Ω max.)
Extended Continuity Test (resistance)	2kΩ, 60kΩ, 300kΩ
Test Current / Open-circuit Voltage	≤ 1mA / ≤ 3.3V
<b>Phase Rotation</b>	
Ph/Ph Voltage	50 to 1000Vac (45 to 400Hz)
<b>General</b>	
Buzzer	Intermittent beep for Voltage Detection, Continuous beep for Continuity
Cable Length	3.3ft (1m)

For more details, download the datasheet or user manual at [www.aemc.com](http://www.aemc.com)

15 Faraday Drive • Dover, NH 03820 USA • (800) 343-1391 • (603) 749-6434 • [www.aemc.com](http://www.aemc.com)

[customerservice@aemc.com](mailto:customerservice@aemc.com) • [techsupport@aemc.com](mailto:techsupport@aemc.com)

Display	LEDs + Backlit Digital Display
Power Supply	2 x AA (LR6) Batteries (included)
Battery Life	5000 ten second measurements approximately
Dimensions	9.0 x 2.4 x 1.5" (228 x 60 x 39mm)
Weight (With Battery)	12.4oz (350g) approximately
Operating Temperature/Humidity	-22 to 140°F (-30 to +60°C) / 20 to 95% RH non-condensing
Storage Temperature/Humidity	-40 to 158°F (-40 to +70°C) / 20 to 95% RH non-condensing
IP Rating	IP 65
Electrical Safety	1000V CAT IV per IEC 61010-1

For more details, download the datasheet or user manual at [www.aemc.com](http://www.aemc.com)

15 Faraday Drive • Dover, NH 03820 USA • (800) 343-1391 • (603) 749-6434 • [www.aemc.com](http://www.aemc.com)  
[customerservice@aemc.com](mailto:customerservice@aemc.com) • [techsupport@aemc.com](mailto:techsupport@aemc.com)

