CABLE TESTERS

CABLE LOCATOR

MODEL 6681

Detects and locates faults in electrical cables, telecommunication cables, live and de-energized conductors buried or in walls

SPECIFICATIONS

MODEL	6681 (TRANSMITTER)	
Display	LCD screen with display of functions and bargraph	
Output Signal Frequency	125kHz	
External Voltage Measurement Range	12 to 300Vac/pc	
Functions	Digital coding of signals for easy signal identification, selection of transmission signal code, flashlight	
Power Supply	9V battery	
Dimension	7.48 x 3.5 x 1.67" (190 x 89 x 42.5mm)	
Weight	15oz (420g) with battery	
Electrical Safety	300V CAT III	

MODEL	6681 (RECEIVER)
Display	Backlit LCD with display of functions and bargraph, transmission code, receiver and transmitter battery-charge status
Detection Depth Single and Pole Application Two and Pole Application Single Loopback Line	0 to 6 ft (0 to 2m) 0 to 1.6 ft (0 to 0.5m) Up to 8.2 ft (2.5m)
Line Voltage Detection	Approximately 0 to 1.3 ft (0 to 0.4m)
Functions	Automatic shutdown, automatic or manual adjustment of reception sensitivity, flashlight
Power Supply	6 x 1.5V AAA batteries
Dimension	9.5 x 3.07 x 1.5" (241.5 x 78 x 38.5mm)
Weight	12oz (360g) with battery
Safety Rating	300V CAT III

PRODUCT INCLUDES

Soft carrying case, set of (2) color-coded (red/black) leads w/4mm banana plugs {1000V CAT III}, set of (2) color-coded (red/black) alligator clips {1000V CAT II}, adapter-110V outlet w/ banana plugs, mini ground rod, 9V battery, (6) AAA batteries and a user manual.







RECEIVER

TRANSMITTER









FEATURES

- · Operates in both single and two-pole modes
- · Locates and traces hidden cables
- · Detects and locates line breaks
- · Detects faults in floor radiant heating systems
- · Detects constricted sections of non-metallic pipes
- · Detects circuit breakers/fuses
- · Detects short circuits
- · Backlight and flashlight functions
- · Compliant with standards electrical safety standard EN 61010-1 and electromagnetic compatibility standard EN 61326-1

CATALOG NO.	DESCRIPTION

Cable Locator Model 6681

2127.85