

AC/DC Current Probe Model MR410



The AEMC® MR Series AC/DC Probes are professional AC/DC current probes designed to extend current measuring capabilities of DMMs, oscilloscopes and other instruments. They are built to the latest safety and performance standards, including the CE Mark. Two different hook-shaped jaws are offered, both permitting the user to “pry” or “hook” onto cables (will accept 2 x 500MCM) or even onto small bus bars.

The MR Series probes use Hall effect technology and measure AC and DC current. The electronics and batteries are self-contained in the handles. The output of the AC/DC probes is 1mV/A and 10mV/A. The Model MR410 measures to 400Aac/600Adc. The Model MR410 is single range with manual zero adjust.

There is no output filtering - True RMS with DC component measurements are possible. Phase shift is excellent, making the Model MR410 well suited for power and power quality applications.

Features

- Measurement range of 400Aac/600Adc
- Distinct jaw shapes to be used for hooking or prying around the conductor
- Auto-zero push button
- Auto off after ten minutes
- Conforms to EN 61010, 600V, CAT III safety standard
- Low phase shift for power measurements
- mV output signals
- Designed for DMMs, recorders, oscilloscopes, power and harmonic meters
- Double Insulation
- CE Mark


Applications

- DC motors
- Batteries
- Automobile engine testing
- Power measuring quality analysis
- Power load monitoring


Specifications

MODEL	MR410
ELECTRICAL	
Nominal Range	400A _{Ac} /600A _{Dc}
Measurement Range	1 to 600A
Output Signal	1mV/A
Accuracy (400A Range)	
1 to 100A	1.5% of Reading ± 1A
100 to 400A	2% of Reading
Phase Shift (400A Range)	
10 to 200A	≤2.5°
200 to 400A	≤2°
Accuracy (600A _{Dc} Range)	
400 to 600A _{Dc} only	2.5% of Reading
Phase Shift (600A Range)	
10 to 100A	-
100 to 400A	-
Overload	1000A _{Ac} and 1500A _{Dc} continuous up to 1kHz
Frequency Range	DC to 10kHz @ -3dB
Load Impedance	>100kΩ/100pF
Working/Common Mode Voltage	600V _{rms}
Battery	9V Alkaline (Approx. 120 hours life)
Output Termination	5 ft Lead
MECHANICAL	
Operating Temperature	14° to 131°F (-10° to 55°C)
Storage Temperature	-40° to 176°F (-40° to 70°C)
Operating Relative Humidity	10 to 35°C 90% ± 5% RH (without condensation), 40 to 55°C 70% ± 5% RH (without condensation)
Zero Adjustment	±10 turn knob at base of case
Jaw Opening	1.2" (31mm)
Maximum Conductor Size	One 1.18" (30mm) or two 0.95" (24mm) or two bus bars 1.2 x 0.4" (31.5 x 10mm)
Dimensions	8.8 x 3.82 x 1.73" (224 x 97 x 44mm)
Weight	15 oz (440g)
Polycarbonate Material	Handles: Polycarbonate + ABS, Gray, UL94 V0. Jaws: Polycarbonate, Red, UL94 V0
SAFETY	
Electrical	EN 61010-2-32
Double Insulation <input type="checkbox"/>	Yes
CE Mark	Yes

Note: Reference conditions: 18°C to 28°C, 20 to 75% RH, external magnetic field <40A/m, no DC component, no external current carrying conductor, test sample centered, 1MΩ ≤ 100pF load, zero adjustment (DC only) DC to 65Hz, battery voltage 9V ± 0.1V.



1. Conductor
2. Zero adjustment knob
3. Lead, 5 ft (1.5m)
4. Safety banana plug \varnothing 4mm
5. Two position range selection switch:
 - On/Off
 - 600A (1mV/A)
6. Green light (on when battery voltage \geq 6.5V)
7. Protective non-slip guard
8. Jaws



Leads:
Double/reinforced
5 ft (1.5m) lead
with safety 4mm
banana plug

ORDERING INFORMATION

	CATALOG NO.
AC/DC Current Probe Model MR410 (Lead – 1mV/A – 600A max).	Cat. #1200.70
Includes a user manual	
Accessories (Optional)	
Banana plug adaptor (to nonrecessed plug)	Cat. #1017.45
Adapter – Banana (Female) – BNC (Male) (XM-BB)	Cat. #2118.46

Contact Us

United States and Canada:

Chauvin Arnoux[®], Inc.
d.b.a. AEMC[®] Instruments
200 Foxborough Blvd.
Foxborough, MA 02035 USA
(508) 698-2115 • Fax (508) 698-2118
www.aemc.com

Customer Support – for placing an order, obtaining price and delivery:
customerservice@aemc.com

Sales Department – for general sales information:
sales@aemc.com

Repair and Calibration Service – for information on repair and calibration, obtaining a user manual:
repair@aemc.com

Technical and Product Application Support – for technical and application support:
techinfo@aemc.com

Webmaster – for information regarding www.aemc.com:
webmaster@aemc.com

South America, Central America, Mexico, Caribbean, Australia and New Zealand:

Chauvin Arnoux[®], Inc.
d.b.a. AEMC[®] Instruments
15 Faraday Drive
Dover, NH 03820 USA
(978) 526-7667 • Fax (978) 526-7605
export@aemc.com
www.aemc.com

All other countries:

Chauvin Arnoux SCA
190, rue Championnet
75876 Paris Cedex 18, France
33 1 44 85 45 28 • Fax 33 1 46 27 73 89
info@chauvin-arnoux.com
www.chauvin-arnoux.com