



600Vac/dc Model L261 & ±850Vdc Model L481

One channel loggers for voltage measuring, monitoring and troubleshooting



► SPECIFICATIONS

MODELS	L261	L481
ELECTRICAL		
Channels	One	
Input Connection	Two recessed 4mm safety banana jacks	
Measurement Range	0 to 600Vac/dc	-850 to ±850Vdc
Resolution	0.1V	
Accuracy (50/60Hz)	0 to 5V: unspecified 5 to 50V: ±(0.5% of Reading + 1V) 50 to 600V: ±(0.5% of Reading + 0.5V)	0 to 5V: unspecified 5 to 50V: ±(0.5% of Reading + 1V) 50 to 850V: ±(0.5% of Reading + 0.5V)
Input Impedance	40MΩ	
Sample Rate	64 samples/cycle	Maximum of 8 per second
Storage Rate	Programmable from 8 every second to 1 every day	
Storage Modes	Start/Stop, FIFO, Extended Recording Mode (XRM™) and Alarm	
Recording Length	15 minutes to 8 weeks, programmable using DataView®	
Memory	240,000 measurements (512KB) The recorded data is stored in non-volatile memory and will be retained even if the battery is low or removed.	
Communication	USB 2.0 optically isolated	
Power Source	2 x 1.5V AA-cell Alkaline batteries (included)	
Battery Life	100 hours to >45 days (dependent on sample rate and recording length)	
MECHANICAL		
Dimensions	4.94 x 2.75 x 1.28" (125 x 70 x 32mm)	
Weight (with battery)	6.4oz (181g)	
Case	UL94-V0	
Vibration	IEC 68-2-6 (1.5mm, 10 to 55Hz)	
Shock	IEC 68-2-27 (30G)	
Drop	IEC 68-2-32 (1m)	

► FEATURES

- TRMS voltage recording up to 600Vac/dc (Model L261)
- Bipolar voltage recording up to ±850Vdc (Model L481)
- AC: 64 samples per cycle and DC: 8 samples per sec (Model L261)
- Programmable storage rates from 8 every second to 1 every day
- 4 user selectable storage modes
- Stores up to 240,000 measurements in non-volatile memory
- Powered by standard Alkaline batteries
- Lightweight, compact, fits anywhere
- 5 LED indicators quickly and clearly display logger status
- Includes FREE DataView® software for data storage, real-time display, analysis and report generation
- Optically isolated USB 2.0 communication cable included
- EN 61010-1; 300V CAT IV; 600V CAT III

► APPLICATIONS (MODEL L261)

- Surge and Sag recording
- Long term supply monitoring
- Industrial, commercial and residential monitoring
- Monitor voltage harmonics
- Find intermittent voltage problems
- Machine monitoring

► APPLICATIONS (MODEL L481)

- Rail voltage monitoring
- Long term supply monitoring
- Find intermittent voltage problems
- Machine monitoring
- Windmill monitoring

► PRODUCT INCLUDES



Set of two color-coded 5ft voltage leads, color-coded alligator clips (red/black), USB type A to 5 pin Mini-B, and USB stick supplied with DataView® software and user manual.

CATALOG NO.	DESCRIPTION
2126.05	Simple Logger® II Model L261 (1-Channel, TRMS, 600Vac/dc, DataView® software)
2126.25	Simple Logger® II Model L481 (1-Channel, DC, ±850V, DataView® software)

