MODELS CA811 & CA813

Features optical sensors that are designed to match the response of the human eye



FEATURES


- · Easy one-hand operation
- · Designed to measure a wide range of lighting types
- · Removable sensor for remote reading
- Measures in foot-candles (fc) or lux (lx)
- · Measures incandescent lighting
- Cosine corrected
- Hold function
- Max function (CA811)
- Peak function (CA813)
- CIE photopic (human eye) response
- 2000-count backlit LCD
- · Lightweight and compact
- · Removable protective sensor cover
- Includes rugged, shockproof, protective and dirt resistant gray cover

PRODUCT INCLUDES

Rugged shockproof protective holster, 9 V battery and user manual.

MODELS	CA811	CA813*		
MEASUREMENTS				
	(20, 200, 2000) fc, 20 kfc			
Range	(20, 200, 2000) lx, 20 klx	(20, 200, 2000) lx, (20, 200) klx		
Display Resolution	0.01 fc or 0.01 lx			
Sensor	Silicon photodiode			
Spectral Response	CIE Photopic Curve			
Accuracy 2856 K Light Source Common Light Source	\pm 5 % of Reading \pm 10 cts \pm 18 % of Reading \pm 2 cts	\pm 5 % of Reading \pm 10 cts \pm 11 % of Reading \pm 2 cts		
Sample Rate	2.5 times per s, nominal			
GENERAL				
Display	3½ digit liquid crystal di	splay <i>(LCD)</i> , 2000-count		
Operating Temperature	(32 to 122) °F (0 to 50) °C, < 80 % RH			
Storage Temperature	(-4 to 140) °F (-20 to 60) °C, (0 to 80) % RH without battery			
Polarity	Automatic			
Power Supply	(1) 9 V Alkaline battery (included)			
Low Battery Indication	- + Displayed when battery voltage is low			
Dimensions	(6.81 x 2.38 x 1.5) in (173 x 60 x 38) mm			
Weight	Approx. 7.55 oz (214 g) (including battery)	Approx. 7.9 oz (224 g) (including battery)		

Consult factory for NIST Calibration prices.



*Note: Model CA813 offers higher sensitivity (200 klx) and has a better spectral response to common light sources Model CA811 is used to measure incandescent lighting.

APPLICATIONS

- Testing for OSHA compliance in workplace, clean room and industrial settings
- · Ambient testing for light-sensitive displays and archives in museums and art galleries

GAT. #	DESCRIPTION
2121.20	Lightmeter Model CA811
2121.21	Lightmeter Model CA813

