

ENVIRONMENTAL TESTERS

LIGHTMETER



MODEL 1110

Features optical sensors that are designed to match the response of the human eye




DataView®



(Free Android™ App available on Google® Play)



SCAN TO
LEARN
MORE



Measure and record multiple measurements to create an illuminance map of the room or area of interest

FEATURES

- User selectable light source, natural, LED or fluorescent
- Spectral error compensation for LED and fluorescent lighting
- Removable light sensor with expandable cable up to 48 inches
- Map mode profiles the illuminance map of the area or room by storing multiple measurements
- Min, Max, and Average measurements stored
- Free app for Android™ from the Google® Play Store
- Spot or continuous recording of up to 1,000,000 measurements stored in 8 MB flash memory
- Blue luminescent backlit display
- User selectable foot-candle (fc) or lux (lx) units
- USB and Bluetooth® communication
- Magnetic mount
- Battery or USB powered
- DataView® graphing and analysis software included

PRODUCT INCLUDES

Soft carrying pouch, 6 ft USB cable (Type A to Type B micro), (3) 1.5 V AA batteries, a printed quick start guide, USB drive with DataView® software and user manual.

CAT. #	DESCRIPTION
2121.71	Lightmeter Data Logger Model 1110

MODEL	1110
Measurement Range	(0.01 to 200,000) lx (0.01 to 18,580) fc
Accuracy	± 3 % of R on incandescent sources ± 6 % of R on LEDs (3000 to 6000) K ± 9 % of R on fluorescent sources
Accuracy with Compensation	LED mode: ± 4 % of R (at 4000 K) Flou mode: ± 4 % of R (type F11, 4000 K)
Display Resolution	0.1 lx (0.1 to 999.9) lx 1 lx (1000 to 9999) lx 10 lx (10,000 to 99.99) lx 100 lx beyond 0.01 fc (0.01 to 99.99) fc 0.1 fc (100.0 to 999.9) fc 1 fc (1000 to 9999) fc 10 fc beyond
Recording	Manual start / stop on the product Short press for MEM: spot recording Long press for REC at the defined default rate Programed recording: start date, recording interval, and end date defined using DataView® software
Other Functions	MIN-AVG-MAX-HOLD
Sampling Rate	Programmable from (1, 2, 5, 10, 20, or 30) s, (2, 5, 10, 15 or 30) min, and 1 hr
MAP mode	The MAP mode can be used to map the lighting on the surface of a room In this case the measurements are saved in the same file
Operating Temperature	(14 to 140) °F (-10 to 60) °C
Storage Temperature	(-4 to 140) °F (-20 to 60) °C
Relative Humidity	Up to 90 % RH

GENERAL

Memory	1,000,000 measurements on each channel (4 MB) Recorded data is stored in non-volatile memory and will be retained even if battery is low or removed
Communication	USB 2.0 and Bluetooth®
Power Supply	(3) 1.5 V AA (LR6) alkaline batteries or USB port (micro-USB adaptor offered as an accessory)
Battery Life	500 h, 3 yrs with 15 min intervals
Dimensions	Case: (5.9 x 2.84 x 1.28) in (150 x 72 x 33) mm Sensor: (2.64 x 2.52 x 1.38) in (67 x 64 x 35) mm
Weight (with battery)	12.2 oz (34 g) with batteries
Case	Polycarbonate

SAFETY

EMC	EN 61326-1
Safety Rating	IEC 61010-1
Ingress Protection	IP50 with USB connector closed and protective cap on sensor
Warranty	2 y

Consult factory for NIST Calibration prices.

ACCESSORIES/REPLACEMENTS

CAT. #2118.65 Soft Carrying Case	CAT. #2122.31 Shockproof Housing
CAT. #2138.66 Cable - 6 ft. USB Type A - Type B micro	CAT. #2153.78 Adapter - US Wall Plug to USB
CAT. #2118.09 General Purpose Carrying Case	CAT. #5000.44 MultiFix Universal Mounting System