

ENVIRONMENTAL TESTERS

AIR QUALITY

MODEL 1510

Monitor CO₂, temperature, and humidity for a healthy environment

Assists with the prevention of COVID 19 by testing indoor air quality. Contact us to learn more.

SPECIFICATIONS

MODEL	1510
CO₂ MEASUREMENT	
Measuring Principle	Non-dispersive infrared (NDIR) technology
Type of Sensor	Double-beam infrared cell sensor
Measurement Range	0 to 5000 ppm
Accuracy (CO ₂)	±50 ppm ±3% of value measured
Response Time, 63%	< 200 seconds
Resolution	1 ppm
TEMPERATURE MEASUREMENT	
Type of Sensor	CMOS
Units	°C or °F
Measurement Range	14° to 140°F (-10° to 60°C)
Accuracy	±0.1°F (±0.5°C)
Resolution	0.1°F (0.1°C)
HUMIDITY MEASUREMENT	
Type of Sensor	Capacitive
Measurement Range	5 to 95% RH
Accuracy	±2% RH
Resolution	0.1% RH
GENERAL	
Recording Interval	Programmable from 1 minute to 2 hours
Storage	> 1 million measurements
Alarm	Yes
Backlighting	Blue - red when in alarm condition
Hold, Min & Max	Yes
Auto Power OFF	Yes (in portable mode only)
Dimensions / Weight	4.92 x 2.58 x 1.26" (125 x 65.5 x 32mm) 6.7oz (190g) with batteries
Power Source	Alkaline batteries: (2) AA or rechargeable battery connection to 120V 60Hz line / USB to wall adapter
Communication	Bluetooth (Class I) wireless communication / USB link; the product is then recognized as a USB drive for easy file transfer
Mounting	Optional padlock wall mount (padlock is not included), optional desktop stand and wall mount holster
DataView® Software	Graphic representation or as table of values, data export, real-time mode calculation of the confinement index with selection of presence periods & report generation
SAFETY	
Safety Rating	IEC 61010-1, 50V CAT II – IEC 61326-1
Ingress Protection	IP40

Consult factory for NIST Calibration prices



DataView®

FEATURES

- CO₂, temperature, and humidity logger
- Free app for Android™ from the Google® Play Store
- Display turns red when any of the measurements are in alarm condition
- Compact and stand-alone: for mounting or portable use
- User-friendly: comfort indicators based on the CO₂, temperature and humidity levels
- Accurate: complies with the latest standards concerning air quality monitoring
- Quick, simple data download using supplied DataView® software
- On-site calibration test module with adapter, tube and software for adjusting the zero and thresholds

PRODUCT INCLUDES

Soft carrying pouch, adapter - US wall plug to USB, 6 ft USB cable, (2) 1.5V AA batteries, printed quick start guide, and a USB drive with DataView® software and a user manual.



ACCESSORIES/REPLACEMENTS

- Catalog #2138.61**
Wall Mount Holster (Gray)
- Catalog #2138.62**
Desktop Stand (White)
- Catalog #2138.63**
Calibration Kit
- Catalog #2138.66**
6 ft USB cable

- Catalog #2138.67**
Wall Mount Holster (White)
- Catalog #2153.78**
Adapter - US Wall Plug to USB
- Catalog #2154.71**
Replacement Carrying Pouch

CATALOG NO.	DESCRIPTION	CATALOG NO.	DESCRIPTION
2138.08	Air Quality Logger Model 1510 (Gray)	2138.09	Air Quality Logger Model 1510 (White)

